

REM-2



(E3/L3) EARTHMOVER/LOADER TIRE

The Double Coin REM-2 Off-The-Road radial features an aggressive self-cleaning tread design. Engineered to deliver a smooth ride and superior traction in all types of terrain, the REM-2 is an OEM Certified OTR with an advanced casing design that promotes retreadability.



PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (INCH)	SECTION WIDTH (INCH)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	TIRE WEIGHT	TIRE TYPE	NOTE
1107147251	17.5R25	REM-2	★	10	5	53	18	34	14.00/1.5	15620lb/73psi	153kg/331lb	T/L	-
1107140251	20.5R25	REM-2	★	10	5	58	21	39	17.00/2.0	20900lb/73psi	229kg/488lb	T/L	-
1107143251	23.5R25	REM-2	★	10	5	64	24	45	19.50/2.5	26730lb/73psi	336kg/719lb	T/L	-
1107146252	26.5R25	REM-2	★	10	5	69	27	47	22.00/3.0	33000lb/73psi	461kg/1020lb	T/L	-
1107167251	17.5R25	REM-2	★★	50	30	53	18	34	14.00/1.5	11990lb/76psi	157kg/338lb	T/L	-
1107167251	17.5R25	REM-2	★★	10	5	53	18	34	14.00/1.5	18700lb/94psi	157kg/338lb	T/L	-
1107160251	20.5R25	REM-2	★★	50	30	58	21	39	17.00/2.0	16060lb/76psi	231kg/491lb	T/L	-
1107160251	20.5R25	REM-2	★★	10	5	58	21	39	17.00/2.0	25300lb/94psi	231kg/491lb	T/L	-
1107163251	23.5R25	REM-2	★★	50	30	64	24	45	19.50/2.5	20350lb/76psi	336kg/721lb	T/L	-
1107163251	23.5R25	REM-2	★★	10	5	64	24	45	19.50/2.5	31900lb/94psi	336kg/721lb	T/L	-
1107166252	26.5R25	REM-2	★★	50	30	69	27	47	22.00/3.0	25300lb/76psi	463kg/1023lb	T/L	-
1107166252	26.5R25	REM-2	★★	10	5	69	27	47	22.00/3.0	40700lb/94psi	463kg/1023lb	T/L	-
1107162955	29.5R25	REM-2	★★	50	30	73	29	50	25.00/3.5	30800lb/76psi	587kg/1274lb	T/L	-
1107162955	29.5R25	REM-2	★★	10	5	73	29	50	25.00/3.5	49280lb/94psi	587kg/1274lb	T/L	-
-	775/65R29	REM-2	★★	50	30	69	30	58	24.00/3.5	26730lb/62psi	-	-	-
-	775/65R29	REM-2	★★	10	5	69	30	58	24.00/3.5	45320lb/94psi	-	-	-
-	875/65R29	REM-2	★★	50	30	74	35	60	28.00/3.5	34100lb/62psi	-	-	-
-	875/65R29	REM-2	★★	10	5	74	35	60	28.00/3.5	56650lb/94psi	-	-	-